

Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers



Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Table of Contents

Introduction	3
600W Phase Adaptive RF Dimmer	4
600W RF Dimmer w/ Neutral Wire	5
600W and 1000W Wired Communication Dimmer w/ Neutral Wire.	6
1000W RF Dimmer w/ Neutral Wire	7
GRAFIK Eye QS Main Unit and Wallbox Power Module.	8
4 Zone Forward Phase Remote Dimming Module	9
4 Zone Phase Adaptive Remote Dimming Module	10
How to calculate wattage when mixing lamp types.	11

Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Dimming light emitting diodes (LEDs) and compact fluorescent (CFL) lamps/fixtures can be challenging, because the variations in driver technology make it difficult to choose the right dimmer for a particular lamp/fixture.

We have put together this list of LED and CFL lamps/fixtures that are compatible with our residential systems products. The lamps/fixtures on this list were approved after testing by Lutron. All controls in this document are UL listed for 150W of approved LED and CFL load per zone. Compatibility is an indication that the lamp/fixture has been evaluated for a basic level of functionality and safe operation to the rated load of the Lutron control.

If you'd like more information on dimming LEDs—including a white paper and product selection tool—please visit www.lutron.com/dimcflled.

Note: We are continuously testing bulbs for compatibility with RadioRA 2 and HomeWorks QS dimmers and updating this list regularly. Not all bulbs listed are compatible with every RadioRA 2 and HomeWorks QS dimming product. Refer to the tables for each specific product to determine compatibility. Please continue to check the list as more bulbs are tested.

Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Bulbs for 600W Phase Adaptive RF Dimmer

Models: RRD-6NA
HQRD-6NA



LED bulbs

Brand	Wattage	Model	Description
Commercial Electric	14.5W	CED6 WW 120 WH	6" Downlight, White
Cree	9.5W	CR6	6" Downlight, 2700k, Edison Base
	9.5W	CR4	4" Downlight, 2700k, Edison Base
	9.5W	CR6-GU24	6" Downlight, 2700k, GU24 Base
EcoSmart	9.5W	ECO4-575L	4" Downlight
	9.5W	ECO-575L	6" Downlight
	18.0W	ECS 38 WW FL 120	PAR38, Warm White, 3000k
	18.0W	ECS 38 CW FL 120	PAR38, Daylight White, 4900k
GE	7.0W	LED7DP20S830/20	PAR20, 3000k, Flood, Silver Base
	10.0W	LED10DP30S830/20	PAR30, 3000k, Short Neck, Silver Base
	10.0W	LED10DP3LS830/20	PAR30, 3000k, Long Neck, Silver Base
Lithonia	7.5W	LK3BMWLED	3" Downlight
	9.0W	LK4BMWLED	4" Downlight
Philips	18.0W	18E26PAR38D-E2	PAR38**
Sylvania	8.0W	LED8PAR20/DIM/827/FL36	PAR20, 2700k, FL
	9.0W	RT4 Fixture	Ultra RT4 4" Downlight
	10.0W	LED10PARS20/DIM//P/930/FL30	PAR20, 9300k
	11.0W	RT6 Fixture	Ultra RT6 6" Downlight**
	15.0W	LED15BR30/DIM/827	R30, 2700k
	15.0W	LED15PAR30/DIM/P/930/FL40	PAR30, 3000k, FL
	18.0W	LED18PAR38LN/DIM/830/NFL25	PAR38, 3000k, NFL**
	18.0W	LED18PAR38LN/DIM/827/FL40	PAR38, 2700k, FL**
	18.0W	LED18PAR38LN/DIM/830/FL40	PAR38, 3000k, FL**
	21.0W	LED21PAR38/DIM/P/930/FL30	PAR38, 3000k, FL



CFL bulbs*

Brand	Wattage	Model	Description
TCP	14W	4R2014TD50K	R20, TrueDim, 5000k
	16W	41316TD30K	A21, TrueDim, 3000k***

* CFLs typically require a warmup period before their full dimming range is achieved.

** Forward phase only

*** Reverse phase only



Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Bulbs for 600W RF Dimmer w/ Neutral Wire

Models: HQRD-6ND



LED bulbs

Brand	Wattage	Model	Description
Commercial Electric	14.5W	CED6 WW 120 WH	6" Downlight, White
Cree	9.5W	CR6	6" Downlight, 2700k, Edison Base
	9.5W	CR4	4" Downlight, 2700k, Edison Base
	9.5W	CR6-GU24	6" Downlight, 2700k, GU24 Base
EcoSmart	9.5W	ECO-575L	6" Downlight
	9.5W	ECO4-575L	4" Downlight
GE	7.0W	LED7DP20S830/20	PAR20, 3000k, Flood, Silver Base
	10.0W	LED10DP3LS830/20	PAR30, 3000k, Long Neck, Silver Base
Lithonia	7.5W	LK3BMWLED	3" Downlight
	9.0W	LK4BMWLED	4" Downlight
	13.0W	LK5BMWLED	5" Downlight
Philips	18.0W	18E26PAR38-E2	PAR38
Sylvania	8.0W	LED8PAR20/DIM/827/FL36	PAR20, 2700k, FL
	10.0W	LED10PARS20/DIM//P/930/FL30	PAR20, 9300k
	11.0W	RT6 Fixture	Ultra RT6 6" Downlight
	15.0W	LED15BR30/DIM/827	R30, 2700k
	15.0W	LED15PAR30LN/DIM/830/FL40	PAR30, 3000k, FL
	15.0W	LED15PAR30LN/DIM/827/FL40	PAR30, 2700k, FL
	15.0W	LED15PAR30LN/DIM/830/NFL25	PAR30, 3000k, NFL
	17.0W	LED17PAR30LN/DIM/P/830/NFL25	PAR30, 3000k, NFL



CFL bulbs*

Brand	Wattage	Model	Description
Philips	20W	EL/A R40 Dim 20W	R40

* CFLs typically require a warmup period before their full dimming range is achieved.

Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Bulbs for 600W and 1000W Wired Communication Dimmer w/ Neutral Wire

Models: HWD-6ND
HWD-10ND



LED bulbs

Brand	Wattage	Model	Description
Commercial Electric	14.5W	CED6 WW 120 WH	6" Downlight, White
Cree	9.5W	CR4	4" Downlight, 2700k, Edison Base
	9.5W	CR6	6" Downlight, 2700k, GU24 Base
	9.5W	CR6-GU24	6" Downlight, 2700k, GU24 Base
EcoSmart	9.5W	ECO4-575L	4" Downlight
	9.5W	ECO-575L	6" Downlight
GE	7.0W	LED7DP20S830/20	PAR20, 3000k, Flood, Silver Base
	10.0W	LED10DP30S830/20	PAR30, 3000k, Short Neck, Silver Base
	10.0W	LED10DP3LS830/20	PAR30, 3000k, Long Neck, Silver Base
Lithonia	7.5W	LK3BMWLED	3" Downlight
	13.0W	LK5BMWLED	5" Downlight
Philips	18.0W	18E26PAR38-E2	PAR38
Sylvania	8.0W	LED8PAR20/DIM/827/FL36	PAR20, 2700k, FL
	10.0W	LED10PARS20/DIM//P/930/FL30	PAR20, 9300k
	15.0W	LED15BR30/DIM/827	R30, 2700k



CFL bulbs*

Brand	Wattage	Model	Description
Philips	20W	EL/A R40 Dim 20W	R40

* CFLs typically require a warmup period before their full dimming range is achieved.

Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Bulbs for 1000W RF Dimmer w/ Neutral Wire

Models: RRD-10ND
HQRD-10ND



LED bulbs

Brand	Wattage	Model	Description
Commercial Electric	14.5W	CED6 WW 120 WH	6" Downlight, White
Cree	9.5W	CR6	6" Downlight, 2700k, Edison Base
	9.5W	CR4	4" Downlight, 2700k, Edison Base
	9.5W	CR6-GU24	6" Downlight, 2700k, GU24 Base
EcoSmart	9.5W	ECO-575L	6" Downlight
	9.5W	ECO4-575L	4" Downlight
GE	7.0W	LED7DP20S830/20	PAR20, 3000k, Flood, Silver Base
	10.0W	LED10DP3LS830/20	PAR30, 3000k, Long Neck, Silver Base
Lithonia	7.5W	LK3BMWLED	3" Downlight
	9.0W	LK4BMWLED	4" Downlight
	13.0W	LK5BMWLED	5" Downlight
Philips	18.0W	18E26PAR38-E2	PAR38
Sylvania	8.0W	LED8PAR20/DIM/827/FL36	PAR20, 2700k, FL
	10.0W	LED10PARS20/DIM//P/930/FL30	PAR20, 9300k
	11.0W	RT6 Fixture	Ultra RT6 6" Downlight
	15.0W	LED15BR30/DIM/827	R30, 2700k
	15.0W	LED15PAR30LN/DIM/830/FL40	PAR30, 3000k, FL
	15.0W	LED15PAR30LN/DIM/827/FL40	PAR30, 2700k, FL
	15.0W	LED15PAR30LN/DIM/830/NFL25	PAR30, 3000k, NFL
	17.0W	LED17PAR30LN/DIM/P/830/NFL25	PAR30, 3000k, NFL
	18.0W	LED18PAR38LN/DIM/830/NFL25	PAR38, 3000k, NFL
	18.0W	LED18PAR38LN/DIM/827/FL40	PAR38, 2700k, FL
	18.0W	LED18PAR38LN/DIM/830/FL40	PAR38, 3000k, FL



CFL bulbs*

Brand	Wattage	Model	Description
Philips	20W	EL/A R40 Dim 20W	R40

* CFLs typically require a warmup period before their full dimming range is achieved.

Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Bulbs for GRAFIK Eye QS Main Unit and Wallbox Power Module

Models: QSGRJ
HQRJ-WPM-6D-120



LED bulbs

Brand	Wattage	Model	Description
Commercial Electric	14.5W	CED6 WW 120 WH	6" Downlight, White
Cree	9.5W	CR6	6" Downlight, 2700k, Edison Base
	9.5W	CR4	4" Downlight, 2700k, Edison Base
	9.5W	CR6-GU24	6" Downlight, 2700k, GU24 Base
EcoSmart	9.5W	ECO-575L	6" Downlight
	9.5W	ECO4-575L	4" Downlight
	18.0W	ECS 38 WW FL 120	PAR38, Warm White, 3000k
	18.0W	ECS 38 CW FL 120	PAR38, Daylight White, 4900k
GE	7.0W	LED7DP20S830/20	PAR20, 3000k, Flood, Silver Base
	10.0W	LED10DP3LS830/20	PAR30, 3000k, Long Neck, Silver Base
Lithonia	7.5W	LK3BMWLED	3" Downlight
	9.0W	LK4BMWLED	4" Downlight
	12.0W	REAL6 D6MW ESL	6" LED Module
	13.0W	LK5BMWLED	5" Downlight
Philips	18.0W	18E26PAR38-E2	PAR38
Sylvania	8.0W	LED8PAR20/DIM/827/FL36	PAR20, 2700k, FL
	10.0W	LED10PARS20/DIM//P/930/FL30	PAR20, 9300k
	15.0W	LED15BR30/DIM/827	R30, 2700k
	18.0W	LED18PAR38LN/DIM/830/NFL25	PAR38, 3000k, FL
	18.0W	LED18PAR38LN/DIM/827/FL40	PAR38, 2700k, FL
	18.0W	LED18PAR38LN/DIM/830/FL40	PAR38, 3000k, FL
	21.0W	LED21PAR38/DIM/P/930/FL30	PAR38, 3000k, FL



CFL bulbs*

Brand	Wattage	Model	Description
TCP	14W	TCP 4R2014TD50K	R20, TrueDim, 5000k
	16W	TCP 41316TD30K	A21, TrueDim, 3000k

* CFLs typically require a warmup period before their full dimming range is achieved.

Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Bulbs for 4 Zone Forward Phase Remote Dimming Module

Models: HW-RPM-4U-120



LED bulbs

Brand	Wattage	Model	Description
Commercial Electric	14.5W	CED6 WW 120 WH	6" Downlight, White
Cree	9.5W	CR6	6" Downlight, 2700k, Edison Base
	9.5W	CR4	4" Downlight, 2700k, Edison Base
	9.5W	CR6-GU24	6" Downlight, 2700k, GU24 Base
EcoSmart	9.5W	ECO4-575L	4" Downlight
	9.5W	ECO-575L	6" Downlight
GE	10.0W	LED10DP30S830/20	PAR30, 3000k, Short Neck, Silver Base
	10.0W	LED10DP3LS830/20	PAR30, 3000k, Long Neck, Silver Base
Lithonia	7.5W	LK3BMWLED	3" Downlight
	9.0W	LK4BMWLED	4" Downlight
	13.0W	LK5BMWLED	5" Downlight
Philips	18.0W	18E26PAR38-E2	PAR38
Sylvania	15.0W	LED15PAR30LN/DIM/830/FL40	PAR30, 3000k, FL
	15.0W	LED15PAR30LN/DIM/827/FL40	PAR30, 2700k, FL
	15.0W	LED15PAR30LN/DIM/830/NFL25	PAR30, 3000k, NFL
	15.0W	LED15BR30/DIM/827	R30, 2700k
	17.0W	LED17PAR30LN/DIM/P/830/NFL25	PAR30, 3000k, NFL
	18.0W	LED18PAR38LN/DIM/830/NFL25	PAR38, 3000k, FL*
	18.0W	LED18PAR38LN/DIM/827/FL40	PAR38, 2700k, FL*
	18.0W	LED18PAR38LN/DIM/830/FL40	PAR38, 3000k, FL*
	21.0W	LED21PAR38/DIM/P/930/FL30	PAR38, 3000k, FL

* Use with LUT-LBX

Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit
www.lutron.com/dimcflled

Bulbs for 4 Zone Phase Adaptive Remote Dimming Module

Models: HW-RPM-4A-120



LED bulbs

Brand	Wattage	Model	Description
Commercial Electric	14.5W	CED6 WW 120 WH	6" Downlight, White
Cree	9.5W	CR4	4" Downlight, 2700k, Edison Base
	9.5W	CR6-GU24	6" Downlight, 2700k, GU24 Base
	9.5W	CR6	6" Downlight, 2700k, Edison Base
EcoSmart	9.5W	ECO4-575L	4" Downlight
	9.5W	ECO-575L	6" Downlight
GE	7.0W	LED7DP20S830/20	PAR20, 3000k, Flood, Silver Base*
	10.0W	LED10DP3LS830/20	PAR30, 3000k, Long Neck, Silver Base*
Lithonia	7.5W	LK3BMWLED	3" Downlight
	9.0W	LK4BMWLED	4" Downlight
	12.0W	REAL6 D6MW ESL	6" LED Module
	13.0W	LK5BMWLED	5" Downlight
Philips	18.0W	18E26PAR38-E2	PAR38
Sylvania	8.0W	LED8PAR20/DIM/827/FL36	PAR20, 2700k, FL
	9.0W	RT4 Fixture	Ultra RT4 4" Downlight
	11.0W	RT6 Fixture	Ultra RT6 6" Downlight**
	15.0W	LED15PAR30LN/DIM/830/FL40	PAR30, 3000k, FL
	15.0W	LED15PAR30LN/DIM/827/FL40	PAR30, 2700k, FL
	15.0W	LED15PAR30LN/DIM/830/NFL25	PAR30, 3000k, NFL
	15.0W	LED15BR30/DIM/827	R30, 2700k
	18.0W	LED18PAR38LN/DIM/830/NFL25	PAR38, 3000k, FL
	18.0W	LED18PAR38LN/DIM/827/FL40	PAR38, 2700k, FL
	18.0W	LED18PAR38LN/DIM/830/FL40	PAR38, 3000k, FL
	21.0W	LED21PAR38/DIM/P/930/FL30	PAR38, 3000k, FL

* Reverse phase only

** Forward phase only



Dimmable CFL & LED bulbs

Approved for use with RadioRA® 2 and HomeWorks® QS dimmers

List updated January 1, 2013
For the most up-to-date list, visit www.lutron.com/dimcflled

How to calculate wattage when mixing lamp types: (example only)

**Total CFL/LED
Wattage Installed**



3 CFL bulbs x 16 W each
= **48 W**

**Maximum Allowable
Incandescent/Halogen Wattage**



6 Incandescent bulbs x 65 W each
= **390 W**

Example 1:

1. I have a single-gang dimmer and 3 CFL bulbs that are 16 W each, totaling 48 W.
2. Because I have 48 W of CFL bulbs installed, I can have up to 400 W of incandescent bulbs also controlled by this dimmer (6 incandescent bulbs that are 65 W each = 390 W)

(Please note this example applies to a single-gang dimmer only)

Single-Gang	Total CFL/LED Wattage Installed		Maximum Allowable Incandescent/Halogen Wattage
	0 W	+	600 W
	1-25 W	+	500 W
	26-50 W	+	400 W
	51-75 W	+	300 W
	76-100 W	+	200 W
	101-125 W	+	100 W
	126-150 W	+	0 W
End of Gang	Total CFL/LED Wattage Installed		Maximum Allowable Incandescent/Halogen Wattage
	0 W	+	500 W
	1-25 W	+	400 W
	26-50 W	+	300 W
	51-75 W	+	200 W
	76-100 W	+	100 W
	101-125 W	+	50 W
	126-150 W	+	0 W
Middle of Gang	Total CFL/LED Wattage Installed		Maximum Allowable Incandescent/Halogen Wattage
	0 W	+	400 W
	1-25 W	+	300 W
	26-50 W	+	200 W
	51-75 W	+	100 W
	76-100 W	+	50 W
	101-125 W	+	0 W
	126-150 W	+	0 W